

HANGCHA GROUP CO., LTD.

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com









Forklift" App



IS045001:2018

YouTube

IS014001:2015

WeChat






 ${\sf HANGCHA\,GROUP\,CO.,LTD.}\ reserves\ the\ right\ to\ make\ any\ changes\ without\ notice\ concerning$ colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.

2WD/4WD Rough **Terrain Forklift**

with capacities of 1,500 to 1,800kg





CONCEPT

The multipurpose concept refers to the capability of the forklift truck to work in many different areas, with a great performance no matter how hard the conditions are.

We studied all the specifications of the best forklifts in the world, specialized in industrial and rough terrain types, determining the characteristics that makes a forklift work well in an industrial environment. After that, we combined such information, to prepare the basis of the design of our product.



INTRODUCTION

Hangcha 1.5~1.8t 2WD/4WD rough terrain forklifts is a tough, compact forklift. It is world renowned for superior performance, economy and longevity.

6 reasons

choose 2WD/4WD Rough Terrain Forklift

- ► RELIABILITY
- **▶ PRODUCTIVITY**
- ► ENVIRONMENTAL FRIENDLINESS
- ► COMFORTABLE OPERATION
- **EASY MAINTENANCE**
- **► HIGH PERFORMANCE**



HANGCHA be with you at every stage

Efficient, reliable solutions for your demands

STAGE V& TIER 4F

With Hangcha you can meet all Stage V/Tier 4f emissions standards which provides customer demands for value, innovation and performance. The technologies include common rail fuel systems, diesel oxidation catalysts (DOC) and diesel particulate filters (DPF). Designed and optimised to every engine model, our forklift truck maximises efficiency and reliability.







Interactive instrument: The instrument adopts 4.0-inch color LCD display with four interactive buttons, and has one CAN bus communication function. The communication protocol is compatible with SAE J1939 standards.

HANGCHA Forklift with StageV and T4F

ı	No.	Capacity	Series	Manufacturer	Engine	Drive power	Model	Emission Std.	Transmission	Power (kw/rpm)
	1	1.5-1.8t	RT	KUBOTA	V2607-CR-E5B	Diesel	CPCD15/18-XW97E-RT2	StageV / Tier4 final	CHINA	37.4/2400
	2	1.5-1.8t	RT	KUBOTA	V2607-CR-E5B	Diesel	CPCD15/18-XW97C-RT4	StageV / Tier4 final	CHINA	37.4/2400

Note: RT means 2WD/4WD Rough Terrain forklift

Powerful/ Efficient/ Reliable



RELIABILITY

The full-floating hydraulic transmission gearbox, with 2WD and 4WD switch function, can provide higher running speed and stronger gradeability;





2WD Rear tyre:27x10-12

Higher specification fork mounting level-2B, more weight can be loaded.

4WD Rear tyre:10.0/75-15.3





2WD/4WD Front tyre:12-16.5



Oscillating steer axle allows either wheel to step over obstacles keeping the truck and load level.

Dual air filters extra capacity combined radiator with serpentine wave and optimized heat dissipation channel enhance the heat dissipation capability to keep engine reliability even in heavy-duty applications.



The differential is specifically designed for rough terrain and features manual differential lock providing ultimate traction during inclement weather conditions and rough operating surfaces, it differential lock prevents power loose when one wheel spins.



PRODUCTIVITY



The new Dynamic load sensing hydraulic steering system contributes to reduce loss of hydraulic and improve energy efficiency.



The new efficiency lighting system employs LED illuminant and new type reflector to reduce energy consumption, improve significantly illumination performance and prolong work time.



COMFORTABLE OPERATION

In developing the rough terrain forklift, comfort and easy operation is always considered, for example, improved vibrating levels, compound engine damper and full floating seat and cabin are all applied.

Comfortable also contribute to

reduced the noise.





1. In addition to rubber damper between overhead and frames, compound engine damper and full floating power train achier flexible connection between frames and driving system, as a result, traveling vibrations and vibrations from the driving system are significantly reduced.



3. Optimized designing structure to offer a good visibilit



2. The extra foot space is provided to reduce operator fatigue significantly, non-slip step makes getting in and out easy an safe. The new designed steering wheel new brake system and the easy-to-operate levers provide total handling operation.



4. The new design mast provides broad forward visibility due to the longer distance between inside mast.



EASY MAINTENANCE



Newly-developed LCD instrument has more comprehensive functions and more stable performance and entirely displays the full truck state, fault code and other important information, which can make the operator more intuitively and conveniently have a better knowledge of truck state and make the maintenance conveniently.



The easy-to-open hook provides quick access to the engine compartment.



Adoption of new generation integrated electric box makes maintenance and repair convenient, layout becomes more reasonable and with better water-proof performance.



Wet brake offers maximum service life for your brake system.

- / The cover on the Panel can be lifted up simply to check the brake fluid.
- / The two-piece design makes the floorboard easy to lift and remove for access to the power train.
- / The fasteners of the radiator cover can be turned easily by hand to enable quick inspections or servicing.





HIGH PERFORMANCE



Maneuverability

The distance to ground is 280mm, it offers greater maneuverability and keep the truck moving in the roughest of applications, and yet we keep a very low center of gravity, by using a distributed weight in the forklift, giving it an excellent stability.



Three forward gears

Suspension hydraulic transmission with three forward gears, top speed reach 25km/h.

Standard specification

- / Suspension transmission
- / Differential lock
- / 2-wheel drive、4-wheel drive system
- / Suspension seat
- / Return oil filter
- / Big capacity aluminum radiator
- / Air filter
- / Rear working light
- / Warning lamp
- / Cover for tilt cylinder
- / Reversing assist grip
- / Wider fork carriage
- / Wider load backrest
- / LED light

Options

- / Cabin
- / Heater
- / Front window
- / L/R mirror
- / Extinguisher
- / Customer painting
- / OPS system
- / Sparkle arrester
- / Purified exhaust system
- / Auxiliary hydraulic valve
- / Front working light
- / Triplex wide view free-lift mast
- / Special forks
- / Weigher system
- / Attachments
- / Net cover of radiator