### **HDS 10/21-4 CLASSIC**

Reliable, easy to operate hot water high-pressure cleaner, with excellent price/performance ratio and equipped with a high-quality crankshaft pump as well as a robust tubular steel frame.













#### Order no.

1.030-911.0


- Robust crankshaft pump
- Outstanding price-performance ratio
- Robust tubular steel frame

| Technical data                          |             |                   |
|---|-------------|-------------------|
| EAN code                                |             | 4054278956145     |
| Current type                            | Ph / V / Hz | 3 / 400 / 50      |
| Flow Rate                               | l/h         | 350 - 1000        |
| Operating pressure                      | bar / MPa   | 30 - 210 / 3 - 21 |
| Max. Pressure                           | bar         | 235               |
| Temperature (supply 12°C)               | °C          | max. 80           |
| Power rating                            | kW          | 8                 |
| Consumption fuel oil                    | kg/h        | 6.4               |
| Heating oil consumption, eco!efficiency | kg/h        | 5.2               |
| Power cable                             | m           | 5                 |
| Fuel tank                               | I           | 30                |
| Weight (with accessories)               | kg          | 128               |
| Weight incl. packaging                  | kg          | 138               |
| Dimensions (L × W × H)                  | mm          | 1075 × 722 × 892  |
|   |             |                   |

Users must receive training on this device.

| Equipment                         |    |               |
|-----------------------------------|----|---------------|
| Trigger gun                       |    | Standard      |
| High-pressure hose length         | m  | 10            |
| High-pressure hose specification  |    | ID 8, 315 bar |
| Spray lance                       | mm | 1050          |
| Power nozzle                      |    |               |
| ANTI!Twist                        |    |               |
| Pressure switch control           |    |               |
| Pole reversing plug (three-phase) |    |               |
| Included in delivery.             |    |               |





#### **Robust and long-lasting**

- Robust crankshaft pump with proven Kärcher quality.
- A robust tubular steel frame reliably protects the machine against damage.
- Good accessibility for easy service and maintenance.



#### Efficient burner engineering

- High degree of efficiency with low emissions and long life.
- $\blacksquare$  Long work applications thanks to 30-I fuel tank.
- In ecolefficiency mode, the machine operates in the most economical temperature range (60 °C) – with full water flow.



### Classic accessories with EASY!Lock connections

- Quick set-up and pack-up plus easy accessory replacement.
- Robust and durable accessories.
- Easy and intuitive to operate.



























| 14 |
|----|

|   |    | Order no.   | Description  |     |  |  |
|---|----|-------------|--|-----|--|--|
| TRIGGER GUNS  |    | ı           |  | -   |  |  |
| Pistol TR 155°C with package                          | 1  | 4.119-002.0 | High-quality Classic spray gun with robust valve. Also suitable for Kärcher hot water high-pressure cleaners.  | 2 - |  |  |
| EASY!Force conversion kit 1 – from high-pressure hose | 2  | 4.111-050.0 | For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle. |     |  |  |
| EASY!Force conversion kit 2 - from machine            | 3  | 4.111-051.0 | Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.      | t [ |  |  |
| EASY!Force conversion kit 3 - high-pressure gun       | 4  | 4.111-052.0 | Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.          |     |  |  |
| SPRAY LANCES  |    |             |  |     |  |  |
| Rotating spray lances                                 |    |             |  |     |  |  |
| Jet pipe TR 1050mm with package, 1050 mm              | 5  | 4.119-008.0 |  |     |  |  |
| LED nozzle light                                      | 6  | 2.680-002.0 | Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.                    | T   |  |  |
| Spray lance, 250 mm, rotatable                        | 7  | 4.112-027.0 | Spray lance, 250 mm, rotatable, ergonomic  |     |  |  |
| Spray lance, 400 mm, rotatable                        | 8  | 4.112-024.0 | Spray lance, 400 mm, rotatable, ergonomic  |     |  |  |
| Spray lance, 600 mm, rotatable                        | 9  | 4.112-007.0 | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  |     |  |  |
| Spray lance, 840 mm, rotatable                        | 10 | 4.112-006.0 | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.  |     |  |  |
| Spray lance, 1550 mm, rotatable                       | 11 | 4.112-018.0 | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   |     |  |  |
| Spray lance, 2050 mm, rotatable                       | 12 | 4.112-021.0 | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.   |     |  |  |
| Spray lance extender, 1000 mm                         | 13 | 4.112-048.0 | Spray lance extension with EASY!Lock connection. Length 1000 mm.   | T   |  |  |
| Double lance  |    |             |  | _   |  |  |
| Double lance, 960 mm                                  | 14 | 2.112-016.0 | 960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).  |     |  |  |





















|   |    |             |   | Т   |
|---|----|-------------|---|-----|
|   |    | 0           | Provided to   |     |
| SPRAY LANCES  |    | Order no.   | Description   | _   |
| Angular spray lance   |    |             |   | _   |
| WC and gutter lance   | 15 | 4.112-029.0 | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.  |     |
| Flexible spray lance  | -  |             |   | Ť   |
| Flexible lance, 1050 mm                                       | 16 | 4.112-035.0 | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.  |     |
| High pressure articulated joint                               | 17 | 4.112-057.0 | For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.   |     |
| Gutter cleaner  |    |             |   |     |
| Gutter cleaning lance   | 18 | 2.112-015.0 | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.   | ı   |
| Undercarriage spray lance                                     |    |             |   |     |
| Underbody lance   | 19 | 4.112-032.0 | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.   |     |
| Additional handle   |    |             |   |     |
| Additional handle for EASY!Lock spray lances                  | 20 | 4.321-380.0 | Comfortable in every situation - the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. |     |
| KÄRCHER POWER NOZZLE  |    |             |   | Ť   |
| Power nozzle spray angle 25°                                  |    |             |   |     |
| Power Nozzle 25°, 050   | 21 | 2.113-023.0 | Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.  | ı   |
| HP nozzle spray angle 0°                                      |    | •           |   |     |
| Power nozzle 0°, 050  | 22 | 2.113-034.0 | High-pressure nozzle with powerful jet for extremely stubborn dirt.   |     |
| Power nozzle spray angle 15°                                  |    |             |   |     |
| Power nozzle 15°, 055   | 23 | 2.113-047.0 | Fan jet nozzle with 15° spray angle suitable for stubborn dirt.   |     |
| Power nozzle spray angle 40°                                  |    |             |   |     |
| Power Nozzle 40°, 050   | 24 | 2.113-054.0 | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.   |     |
| HIGH-PRESSURE HOSES   |    | <u> </u>    |   |     |
| Classic   |    |             |   |     |
| High-pressure hose Classic, 10 m, ID 8, 315 bar × , EASY!Lock | 25 | 4.119-005.0 |   |     |
| Standard with unions on both sides                            |    |             |   |     |
| High-pressure hose, 10 m, ID 10, 220 bar, 2 × EASY!Lock       | 26 | 6.110-041.0 |   |     |
| High-pressure hose, 10 m, ID 8, 315 bar, 2 × EASY!Lock        | 27 | 6.110-031.0 | 10 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating TR22 trigger gur connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.                                 | ] ۱ |
| High-pressure hose, 15 m, ID 8, 315 bar, 2 × EASY!Lock        | 28 | 6.110-030.0 | 15 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.  |     |



### **EQUIPMENT FOR HDS 10/21-4 CLASSIC 1.030-911.0**



















|   |    |             |  | $\top$ |
|---|----|-------------|--|--------|
|   |    |             |  |        |
|   |    | Order no.   | Description  | L      |
| HIGH-PRESSURE HOSES   |    |             |  |        |
| Standard with unions on both sides                                | 1  |             |  |        |
| High-pressure hose, 20 m, ID 8, 315 bar, 2 × EASY!Lock            | 29 | 6.110-032.0 | 20 m high-pressure hose (M 22 $\times$ 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155 $^{\circ}$ C/315 bar.                   |        |
| High-pressure hose, 30 m, ID 8, 315 bar, 2 × EASY!Lock            | 30 | 6.110-014.0 | With rotary coupling, 2 × M 22 × 1.5   |        |
| High-pressure hose, 15 m, ID 10, 220 bar, 2 × EASY!Lock           | 31 | 6.110-042.0 | 15 m high-pressure hose M 22 × 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.   |        |
| High-pressure hose, 20 m, ID 10, 220 bar, 2 × EASY!Lock           | 32 | 6.110-043.0 | with union on both sides, M 22 $\times$ 1.5 with anti-kink protection. NW 10/155 $^{\circ}$ C/220 bar  |        |
| High-pressure hose, 25 m, ID 10, 220 bar, 2 × EASY!Lock           | 33 | 6.110-044.0 |  |        |
| High-pressure hose, 40 m, ID 10, 220 bar, 2 × EASY!Lock           | 34 | 6.110-045.0 |  |        |
| High-pressure hose, 15 m, ID 12, 210 bar, 2 × EASY!Lock           | 35 | 6.110-059.0 | High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. $2x M 22 \times 1.5$ with anti-kink protection.   |        |
| High-pressure hose, 40 m, ID 12, 210 bar, 2 × EASY!Lock           | 36 | 6.110-060.0 |  |        |
| Longlife 400 with unions on both sides                            | -  |             |  |        |
| High-pressure hose Longlife, 1,5 m, ID 8, 400 bar, 2 × EASY!Lock  | 37 | 6.110-024.0 | 1.5 m high-pressure hose (DN 8, M $22 \times 1.5$ ) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M $22 \times 1.5$ ).                    |        |
| High-pressure hose Longlife, 30 m, ID 8, 400 bar, 2 × EASY!Lock   | 38 | 6.110-023.0 | With rotary coupling, 2 × M 22 × 1.5   |        |
| High-pressure hose Longlife, 20 m, ID 8, 400 bar, 2 × EASY!Lock   | 39 | 6.110-027.0 | with rotary coupling, 2 × M 22 × 1.5   |        |
| High-pressure hose Longlife, 15 m, ID 8, 400 bar, 2 × EASY!Lock   | 40 | 6.110-029.0 | With rotary coupling, 2 × M 22 × 1.5   |        |
| Food industry version with unions on both sid                     | es | ·           |  |        |
| High-pressure hose food grade, 10 m, ID 8, 250 bar, 2 × EASY!Lock | 41 | 6.110-051.0 | 10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M $22 \times 1.5$ with anti-kink sleeve.                 |        |
| High-pressure hose food grade, 20 m, ID 8, 250 bar, 2 × EASY!Lock | 42 | 6.110-052.0 | 20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M $22 \times 1.5$ , with kink protection. NW 8/155°C/250 bar. |        |

 $\blacksquare$  Included in delivery.  $\qed$  Available accessories.



























|   |       |             |  | _   |
|---|-------|-------------|--|-----|
|   |       |             |  |     |
|   |       | Order no.   | Description  |     |
| HIGH-PRESSURE HOSES   |       |             |  |     |
| Longlife food industry version with unions on                                     | both  | sides       |  |     |
| High-pressure hose food grade Longlife, 10 m, ID 8, 400 bar, 2 $\times$ EASY!Lock | 43    | 6.110-053.0 | With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.                         |     |
| WEED CONTROL  |       |             |  |     |
| WR 10   | 44    | 2.114-016.0 | In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.                                      |     |
| ECO!BOOSTER   |       |             |  |     |
| eco!Booster TR 050  | 45    | 2.113-088.0 | ecolBooster with 50% higher area performance than the Kärcher power nozzle; ideal for delicate surfaces. For cold and hot water high-pressure cleaners (nozzle size 050).                          |     |
| QUICK CONNECT   |       |             |  |     |
| Quick-fitting pipe union coupler trapezo  | 46    | 2.115-000.0 | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 $\times$ 1.5 internal thread.               |     |
| Quick-fitting pipe union plug nipple tra  | 47    | 2.115-001.0 | Hardened stainless steel male coupling for quick coupling 2.115-000. With M $22 \times 1.5$ external thread.   |     |
| DRUM AND TANK CLEANING  |       |             |  |     |
| Add-on kit mud sucker   | 48    | 2.641-798.0 |  |     |
| ADD-ON KITS   |       |             |  |     |
| Add-on kit float HDS Classic  | 49    | 2.394-003.0 |  |     |
| Add-on kit hour counter   | 50    | 2.853-192.0 |  | Г   |
| OTHER HP ACCESSORIES  |       | <u> </u>    |  | Ė   |
| Jet gun   | 51    | 2.869-067.0 | Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.              | 1 [ |
| DICHTUNGEN FÜR TR-GEWINDE   |       | '           |  |     |
| Spare part set seals TR   | 52    | 2.880-001.0 |  |     |
| ROTARY NOZZLES (DIRT BLASTERS)  |       |             |  |     |
| Dirt blaster, large   |       |             |  |     |
| Dirt blaster Vibrasoft, 050   | 53    | 4.114-066.0 | Vibrasoft rotary nozzle with rotating point jet for ten times greater cleaning performance. Durable dirt blaster thanks to ceramic nozzle. Reduces vibrations by up to 30% for maximum ergonomics. |     |
| Dirt blaster, large, 050  | 54    | 4.114-027.0 | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzland bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.            | e [ |
| MULTIPLE-JET NOZZLES  |       |             |  |     |
| Angle vario nozzle 0°-90°   |       |             |  |     |
| Angled Vario nozzle, 055  | 55    | 4.113-008.0 | Variable angle nozzle for spray angle adjustment from $0^{\circ}$ to $90^{\circ}$ . For easy adjustment to all kinds o soiling and surfaces.   | f [ |
| STEAM NOZZLE / NOZZLE PROTECTOR / ROLLO   | VER N | IOZZLE      |  | Ė   |
| Steam nozzle  |       |             |  |     |
| Steam jet nozzle 50°  | 56    | 4.116-000.0 | Steam jet nozzle with 50°fan jet. For cleaning and thawing in steam stage. For thawing sand and gravel, de-icing formwork material or de-waxing vehicles.  |     |
|   |       | 1           |  |     |

























|  |        |             |   | $\top$ |
|--|--------|-------------|---|--------|
|  |        |             |   |        |
|  |        | Order no.   | Description   |        |
| STEAM NOZZLE / NOZZLE PROTECTOR / ROLL   | OVER N | IOZZLE      |   |        |
| Rollover nozzle holder                   |        | ı           |   |        |
| Ball Nozzle Holder                       | 57     | 4.764-012.0 | Rollover nozzle holder for contactless changeover from pencil jet to fan jet as well as low-pressure detergent injection via knurled nut. Without nozzle insert. (Additional type-specific power nozzle). | : 🗆    |
| NOZZLE UNION / SPACER                    |        |             |   |        |
| Nozzle union                             |        |             |   |        |
| Nozzle screws                            | 58     | 4.112-011.0 | Nozzle screws with protectors for high-pressure and power nozzles   |        |
| PIPE CLEANING                            |        |             |   |        |
| Pipe cleaning hose, ID 6                 |        |             |   |        |
| Hose assembly TR pipe cleaning DN6 max.2 | 59     | 6.110-046.0 | The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).  |        |
| Pipe cleaning hose, DN 6, 20 m, 220 bar  | 60     | 6.110-008.0 | 20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R $1/8$ nozzle).  |        |
| Hose assembly TR pipe cleaning DN6 max.2 | 61     | 6.110-047.0 | The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).  |        |
| Pipe cleaning nozzle                     | _      | <u>'</u>    |   |        |
| Dirt blaster pipe cleaning D21/060       | 62     | 4.765-002.0 | into ancure the passessary forward mayoment as well as convenient handling  |        |
| Dirt blaster pipe cleaning D30/060       | 63     | 4.765-005.0 | jets ensure the necessary forward movement, as well as convenient handling.   |        |
| Nozzle pipe cleaning size 80             | 64     | 5.763-087.0 | Pipe cleaning nozzle with 24 mm diameter. With 4 nozzles tilted back at a 30° angle.  |        |
| Pipe cleaning nozzle                     | 65     | 5.763-015.0 | 16 mm pipe cleaning nozzle with internal thread. Various jet directions for   |        |
|  | 66     | 5.763-016.0 | environmentally-friendly cleaning of blocked drains and pipes.  |        |
|  | 67     | 5.763-017.0 | 30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.  |        |
| FLOOR AND HARD SURFACE CLEANER           | _      |             |   | Н      |
| Hard Surface Cleaner FRV 30              |        |             |   |        |
| Add-on kit dirt trap                     | 68     | 2.642-532.0 | Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.  |        |
| Hard surface cleaner FR 30 ME            |        | I           |   | +      |
| FR 30 ME surface cleaner                 | 69     | 2.111-013.0 | Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.                  |        |
| Hard Surface Cleaner FR 50               | _      | ·           |   |        |
| FR 50 surface cleaner                    | 70     | 2.111-023.0 | Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.   | g      |

 $<sup>\</sup>hfill \square$  Available accessories.

### **KÄRCHER**





























|  |    | Order no.   | Description  |    |
|--|----|-------------|--|----|
| FLOOR AND HARD SURFACE CLEANER                               |    |             |  |    |
| Machine-specific nozzle kit for FR                           | 1  |             |  |    |
| Nozzle kit for FR, 850 l/h - 1100 l/h                        | 71 | 2.640-442.0 | Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (850 to 1100 l/h).  |    |
| Machine-specific nozzle kits for FRV                         |    |             |  | L. |
| Nozzle kit for FRV, 050                                      | 72 | 2.642-433.0 | Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.  |    |
| Hard surface cleaner FRV 30 Me                               |    |             |  |    |
| FRV 30 Me Surface Cleaner                                    | 73 | 2.111-012.0 | Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C. |    |
| Extension hose FRV 30 Me and FRV 50 Me                       | 74 | 4.441-040.0 | 5 m extension hose for FRV 30 Me. Includes connecting adapter.   |    |
| FOAM SYSTEMS   |    | '           |  | Г  |
| Cup foam lance   |    |             |  |    |
| Cup foam lance Advanced 3, 900 l/h - 2500 l/h                | 75 | 4.112-065.0 |  |    |
| Cup foam lance DUO Advanced 3, 900<br>l/h - 2500 l/h         | 76 | 4.112-069.0 |  |    |
| Cup foam lance Basic 3, 900 l/h - 2500 l/h                   | 77 | 4.112-055.0 | For high-pressure cleaners with a flow rate of 900-2500 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.             |    |
| 1-litre cleaning agent container for cup foam lance basic    | 78 | 5.071-414.0 |  |    |
| 1-litre cleaning agent container for cup foam lance advanced | 79 | 6.414-050.0 | Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).  |    |
| Inno Foam Set  |    |             |  | Г  |
| Inno foam kit with detergent injector                        | 80 | 2.112-000.0 | High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For   |    |
| Inno foam kit  | 81 | 2.112-008.0 | use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.   |    |
| Easy Foam Set  |    |             |  | Π  |
| Easy Foam Set with RM injector                               | 82 | 2.112-010.0 | HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for   |    |
| Easy foam set  | 83 | 2.112-011.0 | connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.   |    |
| Nozzle kits for Inno/Easy Foam Set                           |    |             |  |    |
| Nozzle kit 090 Inno/Easy kit 700 - 1000 l/h                  | 84 | 2.111-019.0 | Nozzle kit contains Kärcher power nozzles and nozzle inserts. For Inno/Easy-Foam set 700-1000 l/h. For optimal foam system performance.  |    |

 $<sup>\</sup>hfill \square$  Available accessories.



























|  |        | Order no.   | Description  |   |
|--|--------|-------------|--|---|
| FOAM SYSTEMS   |        |             |  |   |
| Foam nozzle mounting kit   |        |             |  |   |
| Foam nozzle kit  | 85     | 2.112-013.0 | Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.   |   |
| MIXERS AND INJECTORS   |        |             |  |   |
| HP detergent injector  |        |             |  |   |
| Detergent injector for high and low pressure (without nozzles)                       | 86     | 4.637-032.0 | Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.   |   |
| Detergent injector for high pressure   | 87     | 4.637-033.0 | Cleaning agent dosage at high pressure 3 - 5 %   |   |
| Machine-specific nozzle kit with order no. 3.63                                      | 37-170 |             |  |   |
| Nozzle insert trapezoidal thread HDS-GER   | 88     | 4.769-011.0 | For HD/HDS 750 - 1000 l/h. Consists of nozzle insert + HP power nozzle + union   |   |
| Nozzle insert with order no. 3.637-001   | ,      |             |  |   |
| Nozzle insert for Order No. 3.637-001,<br>high-pressure for machines up to 1100 l/h. | 89     | 4.769-003.0 | Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.  |   |
| Low pressure for units rated up to 1100 l/h  | 90     | 4.769-001.0 | For low pressure with machines up to 1.100 l/h   |   |
| COUPLING PARTS   |        | '           |  |   |
| Rotary coupling  |        |             |  |   |
| Rotary coupling  | 91     | 4.111-021.0 | Kårcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use.<br>Connector Easy!Lock. With grip protection.  |   |
| Connector  |        |             |  |   |
| Nozzle connector/screw connector   | 92     | 4.111-022.0 | Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 $\times$ 1.5 and 1x M 18 $\times$ 1.5. |   |
| Y distributor  | 93     | 4.111-024.0 | Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.   |   |
| Short spray unit   | 94     | 4.111-038.0 | For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.  |   |
| Adapter EASY!Lock  | ,      |             |  |   |
| Adapter 1 M22AG-TR22AG   | 95     | 4.111-029.0 | Adapter 1 to connect the old hose with the new hose  |   |
| Adapter 2 M22IG-TR22AG   | 96     | 4.111-030.0 | Adapter 2 to connect the old device with the new hose and the old gun with the new hose  |   |
| Adapter 3 M22IG-TR22AG   | 97     | 4.111-031.0 | Adapter 3 to connect the old gun with the new spray lance and new servo regulator  | Г |
| Adapter M22 - Swivel   | 98     | 4.111-032.0 | M22 × 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.                        |   |

<sup>☐</sup> Available accessories.





























|   |      | 0               | Berninten   |     |
|---|------|-----------------|---|-----|
| COUPLING PARTS                          |      | Order no.       | Description   |     |
| Adapter EASY!Lock                       |      |                 |   |     |
|   | 1 00 | 1 4 4 4 4 000 0 | A destruction of the control of the | Le  |
| Adapter 5 TR22IG-M22AG                  | 99   | 4.111-033.0     | Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance  |     |
| Adapter 6 TR22IG-M22AG                  | 100  | 4.111-034.0     | Adapter 6 to connect the new device with the old hose and the old hose with the new gun   |     |
| Adapter 7 M18IG-TR20AG                  | 101  | 4.111-035.0     | Adapter 7 to connect the old spray lance with the new nozzle  |     |
| Adapter 8 TR20IG-M18AG                  | 102  | 4.111-036.0     | Adapter 8 to connect the new spray lance with the old nozzle  | Γ   |
| Coupler -2xM22x1,5                      | 103  | 4.111-037.0     | Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \times 1.5 \ m$ .  | . [ |
| ADAPTER for replacement TR22IG-M22AG Er | 104  | 4.111-046.0     | Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection  | [   |
| HOSE REELS                              |      |                 |   |     |
| Hose reel add-on kit                    |      |                 |   |     |
| Add-on kit hose reel HDS Classic        | 105  | 2.639-353.0     |   |     |
| FACADE AND SOLAR PANEL CLEANING         |      |                 |   |     |
| Brushes                                 |      |                 |   |     |
| Drive for roller brush 500              | 106  | 4.762-584.0     | Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.   |     |
| Splash guard for roller brush 500       | 107  | 4.762-621.0     | Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.  |     |
| Roller brush 500 soft                   | 108  | 4.762-623.0     | Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.   |     |
| Roller brush 500 medium                 | 109  | 4.762-624.0     | Medium-hard brush attachment for use with hydraulic drive (4.762-584.0), Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.  |     |
| Roller brush 500 hard                   | 110  | 4.762-625.0     | Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.  |     |
| Brush hard                              | 111  | 6.960-133.0     | Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.   |     |
| Brush medium                            | 112  | 6.960-134.0     | Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.  |     |

<sup>☐</sup> Available accessories.























|                                 |          | Order no.   | Description  | L   |  |  |
|---------------------------------|----------|-------------|--|-----|--|--|
| FACADE AND SOLAR PANEL CLEANING |          |             |  |     |  |  |
| Brushes                         | ,        |             |  |     |  |  |
| Brush soft                      | 113      | 6.960-135.0 | For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.                    |     |  |  |
| iSolar 800 Advanced             | 114      | 6.368-094.0 | iSolar 800 water-driven brush head, 800 mm wide, for water flow rates of 700-1,000 l/h. With two contra-rotating disc brushes and flexible angle joint. For photovoltaic systems.                      | ) [ |  |  |
| iSolar 400 Advanced             | 115      | 6.368-092.0 | iSolar 400 brush for water flow rate of 700-1,000 l/h. The water-driven disc brush with a width of 400 mm cleans small to medium-sized photovoltaic systems. Also perfect for use on elevated systems. |     |  |  |
| Telescopic                      |          |             |  |     |  |  |
| TL low pressure adapter         | 116      | 4.580-097.0 | TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.   |     |  |  |
| Telescopic lance TL 7 F         | 117      | 4.762-609.0 | Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.                                 |     |  |  |
| Telescopic lance TL 7 H         | 118      | 4.762-610.0 | Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach.                                   |     |  |  |
| Telescopic lance TL 10 H        | 119      | 4.762-611.0 | Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.          |     |  |  |
| Telescopic lance TL 10 C        | 120      | 4.762-612.0 | Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.                                 |     |  |  |
| Telescopic lance TL 14 C        | 121      | 4.762-613.0 | Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre.<br>Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.               |     |  |  |
| TL high pressure adapter        | 122      | 4.775-154.0 | TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.                   |     |  |  |
| Wasserenthärtung                |          |             |  |     |  |  |
| WS 50                           | 123      | 6.368-463.0 | The mobile WS 50 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.  |     |  |  |
| WS 100                          | 124      | 6.368-464.0 | The mobile WS 100 water softening unit prevents lime residue on clean surfaces. A special ion-exchange resin removes the dissolved limescale from the water.   |     |  |  |
| WS Regenerator                  | 125      | 6.368-465.0 | With the WS Regenerator regeneration system, the softening cartridges of the water softening units WS 50 and WS 100 can be backflushed and regenerated at the push of a button.                        | ; [ |  |  |
| Hoses                           | <u> </u> |             |  |     |  |  |
| Hose solar                      | 126      | 6.392-978.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 7. The outer layer has especially good sliding properties when extending and retracting the telescopic rod.                    |     |  |  |

<sup>☐</sup> Available accessorie





















|  |          |             | Description  |   |
|--|----------|-------------|--|---|
|  |          | Order no.   |  |   |
| FACADE AND SOLAR PANEL CLEANING                                      |          |             |  |   |
| Hoses  |          |             |  |   |
| Hose solar   | 127      | 6.392-977.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 10. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. |   |
|  | 128      | 6.392-976.0 | High-quality, flexible HP hose (with rubber covering) for the iSolar TL 14. The outer layer has especially good sliding properties when extending and retracting the telescopic rod. |   |
| WET BLASTING ATTACHMENT  |          |             |  |   |
| Wet blasting attachment (without nozzle)                             |          |             |  |   |
| Wet blasting attachment with flow control (without nozzles)          | 129      | 4.115-000.0 | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.                                    |   |
| Wet blasting attachment without flow contro<br>nozzles not included) | 130      | 4.115-006.0 | Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.              |   |
| Nozzle pack for wet blasting attachment                              |          | •           |  |   |
| Nozzle pack TR wet jet set 0055                                      | 131      | 2.112-024.0 | Consisting of wet jet nozzle and nozzle insert – only for use in combination with wet jet unit 4.115-000.0   4.115-006.0.  |   |
| Boron carbide nozzle   |          |             |  |   |
| Boron carbide nozzle, for machines as of 100<br>/h                   | 132      | 6.415-084.0 | In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.  |   |
| DRUM AND TANK CLEANING   |          |             |  |   |
| Barrel and tank cleaning   |          |             |  |   |
| Barrel cleaner BC 14/12  | 133      | 2.112-020.0 | The barrel cleaner BC 14/12 is a spray unit for the internal cleaning of containers and drums – in particular oak barrels with a capacity between 225 and 600 liters.                |   |
| Rotary cleaner head M63E   | 134      | 6.751-061.0 |  |   |
| Nozzle kit for HKF 50 spray head (3.631-009                          | .0 / 3.6 | 31-039.0)   |  |   |
| Nozzle 045 for dual nozzle operation HKF 50                          | 135      | 6.415-446.0 | Nozzle for dual-nozzle operation   |   |
| Nozzle 090 for single nozzle operation HKF !                         | 0 136    | 6.415-447.0 | Nozzle for single-nozzle operation   |   |
| Double handle for exact control of the spray nead                    | 137      | 2.863-036.0 | Double handle. Precise control of the spray head   |   |
| Screw plug for using a spray head with one nozzle                    | 138      | 5.411-061.0 | Screw plug for using a spray head with one nozzle  |   |
| WATER CONNECTION   |          | •           |  |   |
| Geka coupling  |          |             |  |   |
| With hose nozzle, R 3/4"   | 139      | 6.388-455.0 | with hose liner  |   |
| With hose nozzle, R 1"   | 140      | 6.388-465.0 | with hose barb   |   |
|  |          |             |  | _ |

<sup>☐</sup> Available accessories.





















|  |     | Order no.   | Description  |      |
|--|-----|-------------|--|------|
|  |     |             |  |      |
| WATER CONNECTION   |     |             |  | +    |
| Geka coupling  |     |             |  |      |
| Hose coupling  | 141 | 6.388-458.0 | with female thread   | [    |
| Suction filter   |     |             |  | Ė    |
| Water filter   | 142 | 6.414-956.0 | Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve   | ] ۱  |
| Suction filter with check valve                              | 143 | 4.730-012.0 | Brass suction filter suitable for ponds, storage tanks, etc. With check valve.   |      |
| Fine-mesh water filter                                       |     | <u> </u>    |  |      |
| Add-on kit water filter universal                            | 144 | 2.637-020.0 |  |      |
| Fine-mesh water filter with adapter                          | 145 | 4.730-102.0 | Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter 1".                                      | ۲,   |
| Fine-mesh water filter, 100 μm, R 1"                         | 146 | 2.638-270.0 | Fine-mesh water filter, $100 \mu m$ , max. temperature $60^{\circ}$ C. Connects to high-pressure cleaner. Protect the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to $1200 l/h$ . Connector $1''$ . | :s [ |
| Water supply hose  |     |             |  |      |
| Water supply hose  | 147 | 4.440-207.0 | NW 19 R1" / R 3/4", up to 85 $^{\circ}$ C, for pick-up   | [    |
|  | 148 | 4.440-270.0 | NW 19 R1" / R1", up to 85 °C   | [    |
| WASHING BRUSHES  |     |             |  | T    |
| Push-on washing brush  |     |             |  |      |
| Push-on wash brush, M 18 × 1.5                               | 149 | 4.113-001.0 | Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6.  |      |
| Rotating washing brush                                       |     | •           |  |      |
| Rotating wash brush for > 800 l/h machines, nylon bristles   | 150 | 4.113-002.0 | Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to $60^{\circ}$ C, M $18 \times 1.5$ (replaceable brush insert).  | [    |
| Rotating wash brush for > 800 l/h machines, natural bristles | 151 | 4.113-005.0 |  | [    |

 $<sup>\</sup>hfill \square$  Available accessories.